

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

AUG 23 3 10 PM '65

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
Fee	
7. Unit Agreement Name	
NONE	
8. Farm or Lease Name	
C. H. Weir "B"	
9. Well No.	
7	
10. Field and Pool, or Wildcat	
*See below	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>
2. Name of Operator
TEXACO Inc.
3. Address of Operator
TEXACO Inc.
4. Location of Well
UNIT LETTER J 1980 FEET FROM THE South LINE AND 2307 FEET FROM THE East LINE, SECTION 11 TOWNSHIP 20-S RANGE 37-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
3596' (D. F.)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 6950'
9 5/8" O. D. Casing Cemented at 1424'

Skaggs Glorieta: Ran 6717' of 2 7/8" O. D. Casing, 6.50 LB, J-55, NEW, and cemented at 6729', plug at 6717'.

Monument Tubb : Ran 6936' of 2 7/8" O. D. Casing, 6.50 LB, J-55, NEW, and cemented at 6948', plug at 6938'.

Skaggs Drinkard: Ran 6938' of 2 7/8" O. D. Casing, 6.50 LB, J-55, NEW, and cemented at 6950', plug at 6943'.

Pump each plug down with 500 gals acetic acid. Cemented above strings of 2 7/8" Casing with 275 Sx. Trinity Lite Wate, plus 530 Sx. Class "C" 4% gel. Tested above strings of 2 7/8" O. D. Casing for 30 minutes with 1500 P. S. I. from 9:00 A. M. to 9:30 A. M. August 21, 1965. Tested O. K. Job complete 9:30 A. M. August 21, 1965.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. E. Jordan TITLE Field Foreman DATE August 23, 1965

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: