

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER ☒ **Water Supply Well**

Name of Operator  
**Gulf Oil Corporation**

Address of Operator  
**Box 670, Hobbs, N.M. 88240**

Location of Well  
UNIT LETTER **C** **660** FEET FROM THE **north** LINE AND **1650** FEET FROM  
THE **west** LINE, SECTION **14** TOWNSHIP **22S** RANGE **35E** RMPM.

5a. Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.

7. Unit Agreement Name  
**Jalmat Field Yates Sand**

8. Form or Lease Name  
**Unit**

9. Well No.  
**125**

10. Field and Pool, or Valued  
**Jalmat**

12. County  
**Lea**

15. Elevation (Show whether DF, RT, GR, etc.)  
**3600' GL**

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4075' PB  
4663' TD. It is proposed to plug and abandon as follows:

Spot 100' cement plug on top of CIBP at 4075'. Pull up to 3975' and circulate hole with abandonment mud. Spot cement plug from 2075' up to 1950'. Pump 200 sacks Class C cement containing 3% CaCl<sub>2</sub> tailed in with 100 sacks Class C plus 50/50 calseal.\* WOC. Tag cement and fill 13-3/8" casing to surface with Class C cement containing 3% CaCl<sub>2</sub> as required. Install dry hole marker and clean location.

\*into casing leak at 108'.

Top of Salt estimated at 1990'  
13-3/8" casing set and cemented at 2131'. Cement circulated.

I, Thereby certify that the information above is true and complete to the best of my knowledge and belief.

DATE 10-15-76 TITLE Area Engineer

APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: