

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBBS OFFICE O.C.C.  
NEW MEXICO OIL CONSERVATION COMMISSION

Nov 23 3 02 PM '65

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <b>E 9438</b>

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator <b>The British-American Oil Producing Company</b>	8. Farm or Lease Name <b>Jalnat Deep</b>
3. Address of Operator <b>P. O. Box 474, Midland, Texas</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>M</b> <b>660</b> FEET FROM THE <b>South</b> LINE AND <b>660</b> FEET FROM THE <b>West</b> LINE, SECTION <b>1</b> TOWNSHIP <b>22-S</b> RANGE <b>35-E</b> NMPM.	10. Field and Pool, or Wildcat <b>Wildcat</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3593' GL</b>	12. County <b>Lea</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

OTHER **Deviate toward vertical to straighten crooked hole.**

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Drilled to 10,094' with deviations as follows: (9-5/8 surface casing at 5524') 9798 - 3-3/4°; 9840 - 4°; 9862 - 4-1/2°; 9893 - 5°; 9924 - 5-3/4°; 9932 - 6°; 9956 - 6-1/2°; 9987 - 7-1/4°; 10,019 - 7-1/2°; 10,051 - 7-1/4°; 10,083 - 7-1/2°.
2. At 6 p.m., 11-21-65, spotted 130 sacks regular cement with 26 sacks sand from 10,094' to 9820'. WOC 12 hours; tagged top of cement at 9820'.
3. WOC 24 hours and dress plug to approximately 9840'.
4. Set whipstock at approximately 9840' and to orient 180° from hole direction and attempt to correct hole toward vertical.

(Verbal permission to perform above work received from Joe D. Ramey 11-22-65.)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED William E. Moore TITLE District Engineer DATE November 22, 1965

APPROVED BY [Signature] TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: