TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

.1 5. LEASE NM-033312	
6. IF INDIAN, ALLOTTEE OR TR	BE NAME
7. UNIT AGREEMENT NAME	

GEOEDGIONE CONTEN	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Government "A"
1. oil gas well other	9. WELL NO.
2. NAME OF OPERATOR Minerals, Inc.	10. FIELD OR WILDCAT NAME Grama Ridge Morrow
3. ADDRESS OF OPERATOR P.O. Box 1320 - Hobbs, New Mexico 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OF
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1650' FNL & 1650' FWL	Sec. 10, T22S, R34E, N.M.P.1 12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Lea NM 14. API NO. 3583 DF, 3585 KB
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	<u> </u>
REQUEST FOR APPROVAL TO: SUBSEQUENT/REPORT/OF:	

REPAIR WELL			(NC	change on Form 9–330.)	JH
PULL OR ALTER CASING	\sqcup			trange on Form 9-330.)	
MULTIPLE COMPLETE			~		
CHANGE ZONES		<u> </u>			
ABANDON*			**V.		
(other)		<u></u> - I'u k	BRITA		
17 DESCRIBE PROPOSED	OR COMPLETED	OPERATIONS (Clea	rly state all	pertinent details, and give pertine	nt

including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/07/85 - 6/17/85 MIRU PU. Swab tstd storage zone interval 12,963 - 12,985'. TOH w/2 3/8" tbg, Model "D" stinger. Set Baker Model "G" RBP @ 12,800' & spotted 250 gal. 10% acetic. TOH. Schlumberger ran GR-CCL & perf. Morrow "X" zone 12,694 - 12,714 w/2 JSPF w/3 3/8" Ultra jet guns. Set Baker Model "C" Fullbore Retrievable PKR @ 12,380' & swabbed well in.

On sales to Llano, Inc. pipeline @ 7:00 PM w/400 MCFPD rate, LP-680 psig, 6/28/85 FTP-2800 psig on 10/64" ck. Well unloading.

FTP-2075 psig, F920 MCF, 40 BO & 83 BWPD on 11/64" ck. 7/08/85

Subsurface Safety Valve. Mailu. and Type	Set @ Ft.
18. I hereby certify native foregoing is true and correct SIGNED	July 9, 1985
(This space for Federal or State office use)	
APPROVED BY ACCEPTED FOR RECORD TITLE DATE .	

JUL 12 1985

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO

JUL 1.6 1985