

UNITED STATES  
DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIPLICATE\*  
(Other instruction  
verse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

DIVISION BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

5. LEASE DESIGNATION AND SERIAL NO

NM 0183703

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

~~LEASING~~ FEDERAL

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

LITTMAN SAN ANDRES

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

SEC. 21, T21S, R38E

12. COUNTY OR PARISH

LEA

13. STATE

NM

2. NAME OF OPERATOR

WARRIOR, INC.

3. ADDRESS OF OPERATOR

C/O P. O. BOX 5970, HOBBS, NEW MEXICO 88241

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below)

At surface

660' FSL, 2072' SWL

14. PERMIT NO.

15. ELEVATION (Show whether DF, RT, GR, etc.)

3522' DF

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. IN ORDER PROPOSED OR COMPLETED OPERATIONS, CLEARLY STATE ALL PERTINENT DETAILS, AND GIVE PERTINENT DATES, INCLUDING ESTIMATED DATE OF STARTING ANY  
PROPOSED WORK. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.\*

AS PER APPROVAL 9-19-89 THE FOLLOWING WORK WAS DONE 10-16 and 10-17, 1989.

10-16 Rigged up Meenar Well Servicing, lay down rods, rigged up to swab - could not cut parafin.

10-17 Made four(4) swab runs, lay down swab, unflanged well. Displaced hole with mud. Came out of hole with tubing. Stand back seven(7) stands. Lay down rest of tubing Rigged up wire line truck. Set CIBP @ 4272'. Perforated four(4) holes @ 460'. Rigged down wire line. Ran cement retainer on tubing. Rigged up Halliburton; established circ. and cemented with 150 sxs. of Class 'C' cement. Circulated 25sxs. Closed in. ND, cut off well head, Installed dry hole marker. Cut off deadman. Rigged down - well P&A'd,

\* PUMPED 150 SX CNT INTO 9 5/8" CSG - 13 3/8" HOLE ANNULUS.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Consulting Engineer

DATE 2-20-90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE 3-6-90

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugback of the well core.  
Lithology and core description  
submitted to the Bureau.

\*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

REC'D

JUL 1 1990

HOBBES OFFICE

RECEIVED

MAR 7 1990

HOBBES OFFICE