

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0183703

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

East Eunice Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Underlig. - San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 21, T-21S, R-38E

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Atlantic Richfield Company

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 2072' FSL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3522' DF

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Completion ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 8-3/4" hole to 10500'. Plugged back with cement to 4965'.
Ran 153 jts 4-1/2" OD 8R 10.5# J-55 ST&C new casing - 4948.68'.
Set at 4961.88' RKB. Cemented w/437 sx Incor + 3/4 of 1% CFR-2.
Plug down at 7:45 PM 3/3/68. Top of cement @ 3950' by temperature
survey. After 87 hours WOC ran 3-7/8" bit and tested 4-1/2" csg
to 2000# for 30 minutes. Held OK and job complete at 11:30 AM
3/7/68. Perforated San Andres 4332-4350 w/2 JSPP (36 holes).
Treated these perforations w/500 gallons mud acid and 2000 gal-
lons 15% HCl LSTNE acid @ 2400# & 3.9 BPM. ISIP 1800 psi.
Swabbed back load. Placed well on rod pump.

18. I hereby certify that foregoing is true and correct

SIGNED O. D. BretchesTITLE Dist. Drly. Supervisor DATE 3-15-68

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

APPROVED

MAR 21 1968

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 5: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid content, not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1961 O-683229

5010-108-01

SUNDRY NOTICES AND REPORTS ON WELLS

DEPARTMENT OF THE INTERIOR
UNITED STATES

GEOLOGICAL SURVEY

USE PREVIOUS EDITION FOR REPORTS ON WELLS
This form is designed for use in submitting reports on wells and is to be used in accordance with the instructions on the back of the form.

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01

Form No. 100-108-01