Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [X] GAS WELL [ ] OTHER

2. NAME OF OPERATOR
PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR
BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
2086' FNL x 1874' FEL Sec. 22 (Unit G, SW/4 NE/4)

5. LEASE DESIGNATION AND SERIAL NO.
LC-031736 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
GILLULLY "B" Federal

9. WELL NO.
13

10. FIELD AND POOL, OR WILDCAT
WEIR DRINKARD

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
22-20-37 NMPM

12. COUNTY OR PARISH
LEA

13. STATE
NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3451' RDB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[ ]	REPAIRING WELL	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[X]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]	(Other)			
(Other)			[ ]				

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Physical abandonment of hole made 7-7-70.
Abandoned well as follows:

Loaded hole w/ mud.

Spotted plug - 35 sx cement @ 6730 (Perfs 6706-6600)
Shot 5½" from 4514-4203 and pulled from 3586.
Spotted 30 sx cement in + out of stub @ 3586'
Shot 9⅞ @ 1490, 1199, and 1101. Pulled.
Spotted 50 sx cement in + out of stub @ 1101'.
" " " " " of 9⅞" shoe @ 324'
" 10 " " @ Surface & erected P + A marker.

Final cleanup shall be made and ground restored to contour.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE AREA SUPERINTENDENT DATE JUL 14 1970

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

SEP 17 1970

J. L. GORDON
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Ov-4- USGS-H
1- AC Jr
1- SUSP
1- RRY
1- WFS

RECEIVED

SEP 0 8 1970

OIL CONSERVATION COMM.
HOBBS, N. M.