

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP STATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 22-1021.
5. LEASE DESIGNATION AND SURVEY NO.
12-031736(6)
6. IF INDIAN, ALLOTTEE OR TRUST NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill, or to deepen or plug back to a different reservoir.
See "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR PAN AMERICAN PETROLEUM CORPORATION	8. FARM OR LEASE NAME SHULLY B Federal
3. ADDRESS OF OPERATOR BOX 68, HOBBS, N. M. 88240	9. WELL NO. 13
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2086' FNL = 1874' FEL Sec. 22 (Unit G, SW 1/4 NE 1/4)	10. FIELD AND POOL, OR WELLS WEIR DRINKARD-OIL
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 22-20-37 NMPM
15. ELEVATIONS (Show whether DF, RT, GR, etc.) RDB-3451	12. COUNTY OR PARISH LEA
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Completion Oper ☒	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 9-2-68, 5 1/2" OD 14#- 15.5# J-55 ST 1/2 Casing was set @ 7805' w/ 450 gal 4% Gel + 600 gal. Inferno Cement. Tested casing w/ 2500 psi for 30 min. Test O.K. After NOC. Sept 72. Ream, perf. Ann @ 7762-86 w/ 25PF & acidized w/ 500 gal 15%. Evaluated. Dry. Set Retainer @ 7712' and set 1/35 52 cement. Perforated also @ 7860-62, 64-66, 68-72, 81-83, 7400-02, 11-14' w/ 25PF & acidized w/ 1500 gal 15%. Evaluated. Dry. Test. Sprung 2 w/ 50 gal fresh. Perforated Drinkard (Ann) 6781-84, 6809-16, 24, 33-38 w/ 25PF. Acidized w/ 3000 gal 15%. Evaluated - DT 2.4 hrs. Flow 7030 x 236 BW. GOR NVA. 4B/64" CN. TPF- 25-100#. Cgr. 34°

TD-7366
PAD-7618

18. I hereby certify that the foregoing is true and correct

SIGNED <u>[Signature]</u>	TITLE AREA SUPERINTENDENT	DATE 9-18-68
---------------------------	----------------------------------	---------------------

(This space for Federal or State office use)

APPROVED BY _____	TITLE _____	APPROVED
CONDITIONS OF APPROVAL, IF ANY:		DATE _____

4-1- USSS-H
1- NSO
1- GUSP
1- RRY

*See Instructions on Reverse Side

SEP 24 1968

J L GORDON
ACTING DISTRICT ENGINEER