

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instruction
reverse side)TE
re

TO O. C. G.

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME NMFU
2. NAME OF OPERATOR Continental Oil Company	8. FARM OR LEASE NAME S.E. M. U. Pione.
3. ADDRESS OF OPERATOR Box 700, Hobbs, N. Mex. 88240	9. WELL NO. 90
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL + EL, of Sec 22, T-20S, R-37E, Dea County, N. Mex.	10. FIELD AND POOL, OR WILDCAT Cass. Shallow Pool
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SUEVEY OR AREA Sec. 22, T-20S, R-37E
15. ELEVATIONS (Show whether DF, RT, CA, etc.) 3531' DF	12. COUNTY OR PARISH Dea
	13. STATE N. Mex.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Drilled 8 3/4" hole to a TD of 7796' and set 93 joints of 5 1/2" J-55 17# casing and 181 joints of 5 1/2" J-55 15.5# casing. Set casing at 7794' and cemented with 700 sx. lite-wt. - with 10# gilsonite plus 700 sacks of class C cement with additives of 6# gilsonite per sx, 3/4% C.F.P.-2 and 3# salt per sack. Tested casing for 30 minutes at 1000#. Tested O.K.

24. H. - 5 Chas. Wilder, Perm. Sec. Hobbs, N. Mex. 88240, File

SIGNED M. E. Yeakley TITLE Adm. Section Chief DATE 1-19-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

*See Instructions on Reverse Side

JAN 20 1969

J L GORDON
ACTING DISTRICT ENGINEER