Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [X] GAS WELL [ ] OTHER

2. NAME OF OPERATOR
Continental Oil Company

3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
660' FSL & EL, of Sec. 22, T-20S, R-37E, in Lea County, N. Mex.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3515 GR (est.)

5. LEASE DESIGNATION AND SERIAL NO.
LC 031736 (6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
N. M. F. U.

8. FARM OR LEASE NAME
Lowe. Penn.

9. WELL NO.
90

10. FIELD AND POOL, OR WILDCAT
Cass Strawn Pool

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 22, T-20S, R-37E

12. COUNTY OR PARISH
Lea

13. STATE
N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[X]	REPAIRING WELL	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[ ]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]	(Other)			
(Other)				(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was spudded at 11:00 A.M. 12-9-68. Drilled 17½" hole to 315' and set 13 3/8" OD 48# H-40 Casing. Cemented casing with 375 sacks of class H cement with 2% Cal. Chl. Tested casing with 1,000 # pressure for 30 minutes. Tested O.K.

USGS-5 Pan Am-Hobbs 2, Atl. Pac 2, Chev. Mid. 2, File

18. I hereby certify that the foregoing is true and correct

SIGNED Robert Gambill TITLE Administrative Section Chief DATE 12-11-68

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
DEC 16 1968
J. L. GORDON
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side