

22883

COUNTY LEA FIELD Wantz STATE NM 30-025-22833
 OPR SOLAR OIL CO. MAP
 1 Owens Federal
 Sec 19, T-21-S, R-38-E CO-ORD
 660' FSL, 660' FWL of Sec.

Spd 12-4-68

Cmp 2-4-69

CLASS

E

CSG & SX - TUBING

9 5/8" at 850' w/510 sx

7" at 7500' w/650 sx

LOGS EL GR RA IND HC A

TD 7500'; PBD 7483'

IP (Abo) Perfs 7034-7457' P 40 BOPD + 85 BW. Pot based on 24 hr
 test, GOR 826, Grav 39.7

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Johnn Drlg. Co. PROP DEPTH 7400' TYPE
 DATE

8-7-69 F.R. 12-12-68; Opr's Elev. 3443' GL
 PD 7400' (Abo)
 Contractor - Johnn Drlg. Co.
 AMEND FIELD NAME, Formerly reported as
 Undesignated
 12-10-68 Drlg. 3350'
 12-12-68 Drlg. 4024' 1m
 12-16-68 Tight
 12-23-68 TD 5985'; Tight
 1-6-69 Tight
 1-14-69 TD 7500'; Tight
 2-24-69 TD 7500'; PBD 7483'; Tstg
 Perf 7316-60', 7395-7457' (overall)
 Acid (7316-7457') 14,000 gals
 Perf 7187-7261' (overall)
 Acid (7187-7261') 9000 gals
 Swbd 44 SS (15% oil) in 6 hrs (7187-7457')

LEA Wantz
SOLAR OIL CO.

NM Sec 19, T-21-S, R-38-E
#1 Owens Federal Page 2

2-24-69

Continued

Perf @ 7034', 7075', 7080', 7090', 7095',
7108', 7116', 7124', 7134', 7149'

Acid (7034-7149') 1500 gals

Frac (7034-7149') 28,000 gals wtr + 36,000# sd

Swbd 68 BF (2% oil) in 10 hrs (7034-7149')

Perf @ 6711', 6716', 6726', 6732', 6738', 6744',
6754', 6764', 6774', 6782', 6787', 6796', 6816',
6820', 6828', 6832', 6835'

4-14-69

TD 7500'; PBD 7483'; Istg

Acid (6711-6835') 2000 gals (15%)

Frac (6711-6835') 33,500 gals + 33,000# sd

8-4-69

TD 7500'; PBD 7483'; COMPLETE

Perf 6711-6835', Will be Potentialied at later
date

8-4-69

Continued

Well Drilled Tight

LOG TOPS: Base Salt 2739', Yates 2908',

Seven Rivers 3162', Queen 3732', Grayburg

3900', San Andres 4314', Glorietta 5566',

Blaineby 5938', Tubb 6530', Drinkard 6700',

Abo 7100'

8-7-69

COMPLETION REPORTED