

SOLAR OIL COMPANY
Keohane #3

4 14 '69

<u>Depth Interval</u>		<u>Treatment</u>
7423' - 7379'	6 $\frac{1}{2}$ " holes	A/8,000 gals. 28% NE, 8,000 gals. 15%
7356' - 7257'	18 $\frac{1}{2}$ " holes	NE & 32,000 gals. water
7233' - 7183'	7 $\frac{1}{2}$ " holes	A/750 gals. 15% NE
7423' - 7183'		Squeezed w/200 sacks Class "C" cement
7012' - 6919'	10 $\frac{1}{2}$ " holes	A/1,000 gals. 15% NEFE
6876' - 6784'	12 $\frac{1}{2}$ " holes	A/1,000 gals. 15% NEFE
7012' - 6784'		F/40,000 gals. brine and 42,500# sand
7012' - 6784'		Squeezed w/200 sacks Class "C" cement
6340' - 6204'	15 $\frac{1}{2}$ " holes	A/1,500 gals. 15% NE, F/30,000 gals. brine & 56,000# sand -
6133' - 5997'	21 $\frac{1}{2}$ " holes	A/2,000 gals. 15% NE, F/33,000 gals. brine & 47,500# sand
5964' - 5922'	6 $\frac{1}{2}$ " holes	A/750 gals. 15% NE, F/20,000 gals. brine & 20,000# sand