

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO. 30-025-22943
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. SWD 818
7. Lease Name or Unit Agreement Name: Royalty Holdings #4
3. Well No. 4
9. Pool name or Wildcat SAN ANDRES

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other Injection Well

2. Name of Operator
SUNDANCE SERVICES INC.

3. Address of Operator
P.O. BOX 1737 EUNICE NM 88231

4. Well Location
Unit Letter A : 660 feet from the North line and 660 feet from the East line
Section 25 Township 21S Range 37East NMPM Lea County NM

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
11 ft. RKB

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Operations will begin on Dec 10, 2001 to convert to SWD

A) MIRU - install BOP

B) Test casing to 1000#'s

C) go in hole with 4 drill collars and tubing

D) drill out bridge plug at 5770'

E) Pull drill collars and tubing out of hole

F) Go in hole with packer to approx. 6240' to test old perfs.


G) Pull up to 5870' to establish pump rate into perfs from 5970'-6217'

H) Squeeze off perfs 5970'-6217'

I) Perf. San Andres from approx 4560'-4730'

J) Establish injection rate

K) Rig down and move in surface equipment



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Donna L. Roach TITLE president DATE 12-5-01

Type or print name Donna L. Roach Telephone No. 394-2511

(This space for State use)

APPROVED BY _____ TITLE _____ DATE _____

Conditions of approval, if any:

DEC 11 2001