Form 9-331
(May 1963)

COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE* (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
LC-031736(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER DRILLING

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR
PAN AMERICAN PETROLEUM CORPORATION

8. FARM OR LEASE NAME
GILLULLY "B" FEDERAL

3. ADDRESS OF OPERATOR
BOX 68, HOBBS, N. M. 88240

9. WELL NO.
14

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
1980' FNL & 1980' FWL Sec. 34 (Unit F, SE/4 NW/4)

10. FIELD AND POOL, OR WILDCAT
WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
34-20-37 NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

12. COUNTY OR PARISH
LEA

13. STATE
N M

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐	WATER SHUT-OFF	☒	REPAIRING WELL	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐	FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐	SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
REPAIR WELL	☐	CHANGE PLANS	☐	(Other) Spudding			☒
(Other)	☐			(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Big Wist Drlg Co. spudded 17½" hole 3:PM, 6-26-69.

On 6-27-69, 13 3/8" OD 48# H-40 ST&C casing was set @ 332' w/ 250 Sx. Incor 4% Gel + 100 Sx. Incor. Cement circ. After WOC 18 hours, tested casing w/ 1000 psi for 30 min. Test O.K.

Reduced hole to 12¼" @ 330' and drilled to 2614' and set 9 5/8" OD 32.3# H-40 ST&C casing @ 2614' w/ 900 Sx. Incor 8% Gel + 200 Sx. Incor. Cement circulated. After WOC 18 hours, tested casing w/ 1500 psi for 30 min. Test O.K.

Reduced hole to 8¾" @ 2614' and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE AREA SUPERINTENDENT DATE JUL 9 1969

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JUL 11 1969
J. L. GORDON
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

004 - USGS - H
1 - NSW
1 - SUSP
1 - RRY