

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate*
(Other Instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
(LEASE DESIGNATION AND SERIAL NO.)COPY TO
MAR 10 1970

LC-045708-b

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR		7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR		8. FARM OR LEASE NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		9. WELL NO.
10. FIELD AND POOL, OR WILDCAT		11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA
12. COUNTY OR PARISH		13. STATE
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, OR, etc.)
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TAUBROS OIL & GAS - SOTAU OIL CO.

Box 5596, Midland, Texas

1980' FN&EL

3504' GR

Sec. 18, T-21-S, R-38-E

Lea

New Mexico

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

confidential

9-24-69 - Spud 12-1/4" hole.

9-25-69 - Ran 9-5/8", 32.30#, H-40 csg. to 872'. Cmtd. w/260 sx. Class 4% gel, 2% CaCl-2 and 100 sx. Class "C", 2% CaCl-2. Cmt. circ. WOC 18 hrs. Tested csg. to 1000# for 30 mins. Held OK.

10-17-69 - Drld. 8-3/4" hole to TD 7650'.

10-19-69 - Ran 7", 23# & 26#, J-55 csg. to 7650'. Cmtd. w/300 sx. Class 8% gel, 5# salt/sk. and 400 sx. Class "C", 2% gel, 3.3# salt/sk. .5% CFR-2 and 8# sand/sk. WOC 18 hrs. Tested to 1000# for 30 mins. Held OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

Production Clerk

DATE

10 December 1969

TITLE

DEC 12 1969

DATE

*See Instructions on Reverse Side