

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| | |
|--------------------------------|---|
| 5a. Indicate Type of Lease | |
| State <input type="checkbox"/> | Fee <input checked="" type="checkbox"/> |
| 5. State Oil & Gas Lease No. | |

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|---|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/> | 7. Unit Agreement Name |
| 2. Name of Operator Hanson Oil Corporation | 8. Farm or Lease Name Mattern |
| 3. Address of Operator P. O. Box 1515, Roswell, New Mexico, 88201 | 9. Well No. 1 |
| 4. Location of Well UNIT LETTER <u>L</u> , <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>30</u> TOWNSHIP <u>21 South</u> RANGE <u>37 East</u> NMPM. | 10. Field and Pool, or Wildcat Undesignated |
| 15. Elevation (Show whether DF, RT, GR, etc.) 3516' GL | 12. County Lea |

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 4-24-70 Commenced drilling at 1:15 P.M.
- 4-25-70 T.D. 309' red beds. W.O.C.
Ran 9 jts. 12-3/4" @ 309' w/250 sx. class C cement.
Cement circulated to the surface.
- 4-26-70 T.D. 309' red beds. W.O.C.
Tested casing @ 1000 lbs. for 30 min. No leaks.
- 4-28-70 T.D. 2680' Anhydrite. W.O.C.
Ran 86 jts. 8-5/8", 24# & 32#, J-55, set @ 2680' w/350 sx. class C cement + 2% CaCl.
- 4-29-70 T.D. 2680' Anhydrite. Drilling plug @ 2680'. W.O.C. - 24 hours.
Tested casing @ 850 lbs. for 30 min. No leaks.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Gerald E. Harrington TITLE Geologist DATE April 29, 1970

APPROVED BY John W. Runyan TITLE Geologist DATE MAY 1 1971

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 3 1970

OIL CONSERVATION COMM.
WASH., D. C.