

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
NM2A

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- Ta'd	7. Unit Agreement Name
2. Name of Operator Sun Exploration and Production Co.	8. Farm or Lease Name State "A" A/C 2
3. Address of Operator P.O. Box 1861, Midland, Texas 79702	9. Well No. 32-Y
4. Location of Well UNIT LETTER L 2050 FEET FROM THE South LINE AND 760 FEET FROM THE West LINE, SECTION 9 TOWNSHIP 22-S RANGE 36-E N.M.P.M.	10. Field and Pool, or Wildcat South Eunice 7 Rvrs Queen
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data.
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER Add perfs and Acdz.

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- MIRU wo rig. Install BOP. POH w/2-3/8 PC tbg & pkr.
- Perf set I 3838-3854 w/1 JSPF (17 holes) w/3-1/8" CG, 12 GC, by Schlumberger GR Sonic log dated 7-19-70 (perfs flat w/Schlumberger GR-N-CCL dated 7-27-70).
- RIH w/4-1/2" RDG pkr on 2-3/8 WS. Spot 1/2 bbl 15% NEFE 3854-3812. Raise and set pkr at 3790. Attempt to load annulus. Acdz perfs w/1500 gals 15% NEFE. Drop 25 RCN ball sealers spaced throughout. Pump at 4-5 BPM.
- Swab back load and evaluate FE. Lwr pkr through perfs. POH w/WS and pkr.
- Plug back w/sd to 3835 w/ WL dump bailer. Perf set II 3798-3828 w/1 JSPF (31 holes). W/3-1/8" CG, 12 GC, by Schlumberger GR-Sonic log dated 7-19-70 (perfs flat w/Schlumberger GR-N-CCL dated 7-27-70).
- RIH w/RDG pkr on WS. Spot 1/2 bbl 15% NEFE 3828-3797. PUH and set pkr at 3785. Attempt to load annulus. Acdz perfs w/3000 gals 15% NEFE. Drop 47 RCN ball sealers spaced throughout. Pump at 4-5 BPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED De Ann Kemp TITLE Sr. Acct. Asst.

DATE 5-15-84

ORIGINAL FILED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAY 21 1984

RECEIVED

MAY 18 1984

O.C.D.
HOBBS OFFICE