DISTRIBUTION	NEW MEXICO OIL CONSERVATION COMMISSION		Form C-103 Supersedes Old C-102 and C-103 Effective 1-1-65
U.S.G.S. LAND OFFICE OPERATOR	PAGE 1 o	f 2	Sa. Indicate Type of Lease State X Fee 5. State Oil & Gas Lease No. L-2950
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)			7, Unit Agreement Name
OIL X GAS OTHER-			8. Farm or Lease Name
Mewbourne Oil Company 3. Address of Operator P. O. Box 7698, Tyler, Texas 75711			Gulf-State 9. Well No. 1
4. Location of Well UNIT LETTER E 1980 FEET FROM THE NORTH LINE AND 330 FEET FROM			10. Field and Pool, or Wildcat
THE West Line, SECTION 36 TOWNSHIP 20 South RANGE 38 East NMPM.			
15. Elevation (Show whether DF, RT, CR, etc.) 3570 GL			12. County Lea
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	PLUG AND ABANDON	REMEDIAL WORK COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JQB	ALTERING CASING PLUG AND ABANDONMENT
OTHER			
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.			
8 holes; 7150- 6965-68', 4 ho 6761', 1 hole 6731', 1 hole	-52', 3 holes; 7136 -37',	2 holes; 7098-7100', 3 6930-38', 9 holes. Per 1 hole; 6746-48', 3 hol 00', 4 holes; 6673', 1	hole; 6666', 1 hole;
perfs from 709 at 5.5 BPM, M Reset RBP at 7 7098-7184' and 1700# at 6.0 B	RBP. Set RBP at 7225'. 98-7184' with 3200 gals in 0# at 3.5 BPM, Avg 4007225' and tested to 20006d 6930-7040' with 4500 gals BPM, Min 700# at 6.1 BPM 440 bbl load to recover	15% NE-FE acid + 30 bal 0# at 5 BPM. ISDP vacuu #. Set packer at 6854' als 15% NE-FE acid + 11 , Avg 1400# at 6.0 BPM.	1 sealers. Max PP 600# m. Had good ball action Acidized perfs from 2 ball sealers. Max PP
acidized Tubb press 3750#. M ISDP 2000#, 5	from 6612-6761'w/3000 ga Max 5000#, Min 2800# at 2 Mins 2000#, 10 mins 2000 . 123 bbls load to recover	als 15% NE-FE acid + 60 2.8 BPM, Avg 4000# at 4 0#, 15 mins 1975#, RD W	s. Set packer at 6515' and ball sealers. Breakdown BPM. Had good ball action estern. Opened well up.
SIGNED Daylouth	9	gr. Oprns. Secretary	DATE 9/15/87
ORIGINAL SIGNED BY JERRY SEXTON			MAR 2 9 1988
APPROVED BY DISTRICT I SUPERVISOR TITLE DATE DATE			