

WRS COMPLETION REPORT

COMPLETIONS SEC 36 TWP 20S RGE 38E
PI# 30-T-0013 12/12/88 30-025-24085-0002 PAGE 1

NMEX LEA * 1980FNL 330FWL SEC SW NW
STATE COUNTY FOOTAGE SPOT
MEWBOURNE OIL D X DO
OPERATOR: WELL CLASS INIT FIN
1 GULF-STATE
WELL NO LEASE NAME
3570GR D-K
OPER ELIV FIELD/POOL/AREA
API 30-025-24085-0002

LEASE TYPE/NO. PERMIT OR WELL I.D. NO. 301LWO
08/26/1987 03/15/1988 WO-UNIT
SPUD DATE COMP DATE TYPE TOOL STATUS
7400 ABO WELEX DRLG
PROJ. DPTH PROJ. FORM CONTRACTOR
DTD 7420 PB 7400 OTD 7420 FM/TD ABO
DRILLER T.D. LOG T.D. PLUG BACK TO OLD T.D. FORM T.D.

LOCATION DESCRIPTION

7 MI S NADINE, NM

TUBING DATA

TBG 2 3/8 AT 7304

INITIAL POTENTIAL

IPP 1BOPD 4 MCFD 4BW 24HRS
TUBE PERF W/ 30/IT 6612- 6761 GROSS
GTY, GOR-NO DETAIL

FIELD /RESERVOIR
WARREN /TUBB

IPP 1BOPD 1 MCFD 4BW 24HRS
ABO PERF W/ 27/IT 6930- 7040
GTY, GOR-NO DETAIL

FIELD /RESERVOIR
WARREN EAST /DRINKARD

IPP 2BOPD 3 MCFD 10BW 24HRS
ABO PERF W/ 21/IT 7098- 7184
PERF 7098- 7184
GTY, GOR-NO DETAIL

FIELD /RESERVOIR
D-K /ABO

CONTINUED IC# 300257043888

Petroleum Information

Copyrighted 1988
Petroleum
Information Corporation

EB a company of
The Dun & Bradstreet Corporation

PI-WRS-GE
Form No 18

COMPLETIONS
PI# 30-T-0013 12/12/88 SEC 36 TWP 20S RGE 38E
30-025-24085-0002 PAGE 2

MEWBOURNE OIL
1

GULF-STATE

D X DO

PRODUCTION TEST DATA

BLINEBRY PERF
PERF 6012- 6311
CSPK

6012- 6311

6012- 6311

ABO PERF W/ 48/IT 6930- 7184 GROSS
PERF 6930- 6938 6956- 6960 6965- 6968 7032- 7040
PERF 7098- 7100 7136- 7137 7150- 7152 7165- 7172
PERF 7182- 7184
ACID 7098- 7184 3200GALS
15% NEFE
ACID 6930- 7184 4500GALS
15% NEFE

TUBB PERF W/ 30/IT 6612- 6761 GROSS
PERF 6612- 6617 6620- 6622 6633- 6633 6659- 6659
PERF 6666- 6666 6673- 6673 6697- 6700 6703- 6703
PERF 6731- 6731 6737- 6741 6746- 6748 6750- 6750
PERF 6755- 6755 6761- 6761
ACID 6612- 6761 3000GALS
15% NEFE

DRILLING PROGRESS DETAILS

MEWBOURNE OIL
BOX 520
HOBBS, NM 88241
505-393-5905
OWWO: OLD INFO: FORMERLY MARK PRODUCTION CO
#1 GULF-STATE. ELEV 3570 GR. SPUD 8/19/72.
8 5/8 @ 1675 W/730 SX, 4 1/2 @ 7420 W/400 SX.
OTD 7420. PB 6800. COMP 8/22/72.
IPP 40 BO, 1 BWP. PROD ZONE: BLINEBRY
6012-6311.
FIELD: WARREN, WARREN EAST & D-K
12/05 LOC/1988/
12/05 DO CIBP @ 6800
12/05 7420 TD, PB 7400
COMP 3/15/88, IPP 1 BO, 4 MCFG, 4 BWP,
GOR (NR), GTY (NR)
PROD ZONE - TUBB 6612-6761
COMP 3/15/88, IPP 1 BO, 1 MCFG, 4 BWP,

CONTINUED

COMPLETIONS SEC 36 TWP 20S RGE 38E
PI# 30-T-0013 12/12/88 30-025-24085-0002 PAGE 3

MEWBOURNE OIL
1

GULF-STATE

D X DO

DRILLING PROGRESS DETAILS

GOR (NR), GTY (NR)
PROD ZONE - DRINKARD 6930-7040
COMP 3/15/88, IPP 2 BO, 3 MCFG, 10 BWPD,
GOR (NR), GTY (NR)
PROD ZONE - ABO 7098-7184
(TRIPLE PRODUCER)
FIRST REPORT & COMPLETION

OWWO

COUNTY LEA FIELD Blinebry STATE NM 30-025-24085

OPR MARK PRODUCTION CO. MAP

1 Gulf-State

Sec 36, T-20-S, R-38-E

CO-ORD

1980' FNL, 330' FWL of Sec

Re-Spd 8-19-72

CLASS

EL

Re-Cmp 8-22-72

FORMATION

DATUM

FORMATION

DATUM

CSG & SX - TUBING

8 5/8" at 1675' w/730 sx

4 1/2" at 7420' w/400 sx

LOGS EL GR RA IND MC A

TD 7420'; PBD 6800'

IP (Blinebry) Perfs 6012-6311' P 40 BOPD + 1 BW. Pot based
on 24 hr test. GOR 1500; Grav NR

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.
DATE

PROP DEPTH 6800' TYPE WO

F.R.C. 10-14-72; Opr's Elev. 3570' GL
PD 6800' WO (Blinebry)
(Orig. comp 6-3-72 thru (Abo) Perfs 6979-7348',
OTD 7420')
10-9-72 TD 7420'; PBD 6800'; COMPLETE
PB to 6800'
Perf 6012-6311' (overall) w/40 shots
Acid (6012-6311') 3000 gals
Frac (6012-6311') 40,000 gals jelled brine +
66,000# sd
10-14-72 COMPLETION REPORTED

5-23-72 Continued
DST 6730-6980', open 1 hr, rec 1130' gas in
drill pipe + 510' HGCM w/trace oil, 1 hr ISIP
1175#, FP 280-364#, 2 hr FSIP 1425#
DST 6975-7050', open 1 hr, GTS in 40 mins @
TSTM, rec 1025' GCM w/trace oil, 1 hr ISIP 2358#,
FP 210-318#, 2 hr FSIP 2358#
5-31-72 TD 7420'; Prep Perf
6-5-72 TD 7420'; Flwg 1d
Perf 6975-7348' (overall) w/26 shots
Acid (6975-7348') 18,000 gals
6-12-72 TD 7420'; Tstg
6-19-72 TD 7420'; COMPLETE
LOG TOPS: Anhydrite 1620', Yates 2890', Seven
Rivers 3135', Queen 3700', Grayburg 3905',

6-19-72 Continued
San Andres 4295', Glorieta 5566', Padlock
5685', Blinbry 6005', Tubb 6570', Driskard 6810',
Abo 7090'
6-24-72 COMPLETION REPORTED

STATE LEA FIELD 2-K STATE NM 30-025-24085
 MARK PRODUCTION CO.
 1 Gulf - State
 Sec 36, T-20-S, R-33-E
 1980' FNL, 330' FWL of Sec
 Spd 5-3-72
 Cmp 6-3-72

C&S & SX - TUBING
 8 5/8" at 1675' w/730 sx
 4 1/2" at 7420' w/400 sx

LOGS FL GR RA IND HC A

TD 7420'

IP (Abo) Perfs 6979-7348' F 37 BOPD + 1 BW. Pot based on 24 hr
 test thru 16/64" chk; GOR 5730; Grav 35.6; CP PWT; CP 1218

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

DATE Tri-Service PROP DEPTH 7500' RT

F.R. 4-10-72; Opr's Elev. 3570' GL
 PD 7500' RT (Abo)
 Contractor- Tri-Service
 5-8-72 Drlg. 3745'
 5-15-72 Drlg. 6000'
 5-23-72 Drlg. 7250'
 DST 5560-5600', open 1 hr, rec 90' WCM, 1 hr
 ISIP 2261#, FP 56-84#, 1 hr 30 min FSIP 2177#
 HP 2930-2930#
 DST 6005-6250', open 1 hr, rec 330' WCM w/trace
 oil, 1 hr ISIP 2094#, FP 196-280#, 1 hr FSIP
 2205#, HP 3418-3418#
 DST 6250-6500', open 30 min, rec 30' WCM, no shows,
 1 hr ISIP 2433#, FP 87-87#, 1 hr FSIP 2417#, HP
 3383-3399#