

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation	8. Farm or Lease Name H. T. Mattern (NCT-B)
3. Address of Operator Box 670, Hobbs, New Mexico 88240	9. Well No. 17
4. Location of Well UNIT LETTER <u>C</u> , <u>380</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>31</u> TOWNSHIP <u>21-S</u> RANGE <u>37-E</u> NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moran Drilling Company spudded 11" surface hole at 2:00 PM, June 12, 1972. Drilled to 1230'. Ran 40 joints, 1212' of 8-5/8" OD 24# J-55 ST&C casing set and cemented at 1226' with 275 sacks of Class C cement with 4% gel & 2% Ca Cl2 and 100 sacks of Class C neat with 2% Ca Cl2. Cement circulated. WOC & NU 24 hours. Tested casing with 1100#, 30 minutes, OK.

Started drilling 7-7/8" hole at 1230' at 1:00 PM, June 14, 1972.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. D. Kallinger TITLE Area Engineer DATE June 15, 1972

Orig. Signed by  
John Runyan  
Geologist

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE JUN 16 1972

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 10 1972

OIL CONSERVATION COMM.  
HOBBS, N. M.