

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

N. M. XICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDARY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR NOTICES TO LESSEES OR TO LESSEES OF WELLS IN A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO PRODUCE OIL OR GAS FROM A DIFFERENT RESERVOIR.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Amerada Hess Corporation

Address of Operator
Drawer D, Monument, New Mexico 88265

Location of Well
UNIT LETTER **0** **800** FEET FROM THE **South** LINE AND **1980** FEET FROM
THE **East** LINE, SECTION **16** TOWNSHIP **20 S.** RANGE **37 E.** NMPLA.

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
NM-A-1469

7. Unit Agreement Date

8. Form of Lease Name
State "0"

9. Well No.
5

10. Field and Pool, or Widened
Monument - Paddock

11. Elevation (Show whether DF, RT, GR, etc.)
3532' GR

12. County
Lea

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER Temporary Abandonment ☒

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

May 2, 1978

Pulled production equipment. Ran 4-1/4" bit and checked fill inside 5" liner at 5188'. Ran bridge plug and packer and set bridge plug at 5183' and packer at 5158'. Swab tested 5" liner perfs from 5173' to 5178'. Re-set bridge plug at 5171' and packer at 5097' and swab tested 5" liner perfs from 5138' to 5151'. Re-ran pump and rods and tested 5" liner perfs from 5138' to 5151'. Dowell pumped 500 gal. scale converter down casing and circulated same 48 hours. Dowell acidized 5" liner perfs from 5138' to 5151' w/1500 gal. 15% acid w/additives and flushed w/155 bbls. 2% KCl water and resumed pumping. Pulled and laid down production equipment and closed all valves and temporarily abandoned.

I, E. B. Fisher, Title Supv. Admin. Serv., DATE May 3, 1978

Orig. Signed by Jerry Sexton, TITLE Dist. L. Supv., DATE MAY 8 1978

COPIES 5/8/79