

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM 86148

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cleary AKC Federal #1

9. API Well No.

30-025-24823

10. Field and Pool, or Exploratory Area

Wildcat Delaware

11. County or Parish, State

Lea, NM

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well

☐ Gas Well

☐ Other

RE-ENTRY

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit J, 1980' FSL, 1980' FEL, Sec. 17-T22S-R32E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Re-Entry

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12-17-91. Cut off dry hole marker. RUPU. Wash over dry hole marker. Ran spear to catch dry hole marker. Tagged 2nd plug at 681'. Drilled on plug. Drilled out cement plug from 871-1061'. Tagged 3rd plug at 4450'. Drilled out plug from 4450-4630'. Tagged cement 4716-4914'. Ran tubing to 7363'. Washed to 9620'. Tagged plug. Conditioned mud. POH.  
12-24-91. Ran 5-1/2" casing 15.5# and 17# J-55 LT&C set 9617'. Float collar set 9535' DV tool set 7611'. Cemented 1st stage w/902 sacks. ND, set slips and cut off 5 1/2" casing. TIH with bit, stabilizer, drill collars and 2-7/8" tubing to DV tool at 7611'. RU and drill out DV tool. TIH and cleaned out to float collar. TOH w/2-7/8" tubing, drill collars, stabilizer and bit. TIH with bit, scraper and 2-7/8" tubing to float collar. Circulated casing with 2% KCL water. TOH with 2-7/8" tubing, scraper and bit. Logged well. TIH with bit, drill collars and 2-7/8" tubing to float collar at 9535'. RU and drill out float collar and 20' of cement. Circulate hole clean with 2% KCL water. TOH w/tubing, drill collar and bit. Perforated 9474-9533' w/26 - .42" holes (2 SPF) as follows: 9474, 79, 84, 89, 93, 97, 9502, 06, 10, 13, 20, 28 and 9533'. Acidized perms 9474-9533' w/4200 gals 20% NEFE acid.

14. I hereby certify that the foregoing is true and correct

Signature [Signature]

Title Production Supervisor

Date 1-5-92

(This space for Federal or State office use)

Approved by \_\_\_\_\_

Title \_\_\_\_\_

Date \_\_\_\_\_

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side