Form	9-331
(May	1963

UNIT") STATES UNIT STATES SUBMIT IN TRIPLIC (Other Instructions verse side)

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS
--------	---------	-----	----------------	----	-------

CHANGE PLANS

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NM0554776

(Do not use this form Use	for proposals to drill or to deepen or n "APPLICATION FOR PERMIT—" for s	olng back to a different monormain	
OIL GAS WELL OTHER			7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR			8. FARM OR LEASE NAME
R. J. Zonne			NAME OF THE PARTY
R. J. ZONNE 3. ADDRESS OF OPERATOR			Federal 17
4444			9. WELL NO.
1306 Gihls To	wer West Midland, Te	exas 79701	1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)			10. FIELD AND POOL, OR WILDCAT
At surface		···	Pod Tank Manney Co-
.1980' FS & EL	Red Tank - Morrow Gas 11. SEC., T., B., M., OR BLE. AND		
	, 66661011 17 (61116 07),	1-22-5, N-32-L, NIMPM	SURVEY OR AREA
		".	Sec. 17, T-22-S,
14. PERMIT NO	15. ELEVATIONS (Show wheth		R-32-E, NMPM
	13. ELEVATIONS (Show wheth	er DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	3680.91 GR	lD	Lea New Mexico
16. Ci	neck Appropriate Box To Indicat	te Nature of Notice, Report, or (11911 1191
NOTICE OF INTENTION TO: SUBSEQU		UENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANCE BLANC		-

(Nore: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

7-30-74

(Other)

Dug rat hole and mouse hole. Set 26" conductor @ 30'.

Cemented with Redi Mix. MIRU Rotary tools.

7-31-74

Spud $12\frac{1}{4}$ " hole @ 11:30 P.M. Drilling surface with water.

8-4-74

512'

Anhydrite - WOC - Ran 12 jts. 16" csg. set @ 512'(RKB) Set Halliburton Float Collar @ 469'. Cemented w/480 SK Howco lite w/¼# per SK flocele, 2# salt, followed with 300 SK Class 'C' w/2% CaCl2. Circulated about 80 SK. Job complete @ 12:15 A.M. 8-4-74. WOC 18 hrs. Pressure tested casing to 500 psi for 30 min. Held 0K.

18. I hereby ce the trat property is true and correct		
SIGNED Foy W. Boyo		DATE 8-8-74
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	ACCEPTED FUT RECORD

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY HOBBS, NEW MEXICO