	UN! D STATES PARTMEN OF THE INTI GEOLOGICAL SURVEY	, 	NM	Bodget Burchin in definition A: 1-2379	VD KURTAD NO
	NOTICES AND REPORT or proposals to drill or to deepen or p APPLICATION FOR PERMIT-" for su				
2. NAME OF OPERATOR	OTHER	Deeren		AGREEMENT NAME	E
Gulf Oll Corporat 3. ADDRESS OF OPERATOR	10n	<u></u> []) []] []]]]]]]]]]]]]]]]]]]		Ington A Fe	ederal .
See also space 11 below.)	ew Mexico 88240 location clearly and in accordance with			L AND POOL, OR	WEDDCAT
At surface 660' FNL & 1980' F	WL, Section 25, 22-S, 3	HOBBS, NEW MEXICO 1 <b>2-e</b>	-Wild 11. sec s	Cat L, T., R., M., OR BLI SUBVEY OR AREA	K. AND
14. PERMIT NO.	15. ELEVATIONS (Show wheth	er DF, RT, GR, etc.)	Sec. 12. COI	25, 22-S	32- <u>F</u> 13. STATE
	3	764' GL	Lea		New Maxic
16. Ch	neck Appropriate Box To Indica	te Nature of Notice, Report,	or Other Do	ata	
NOTICE	OF INTENTION TO :	801	BBRQUENT REPO	DET OF:	لم معدد سر
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	xxx	REPAIRING WE	ii
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT Shooting or acidizing		ALTERING CAS ABANDONMENT	
REPAIR WELL	ABANDON*	(Other)	d		
(Other)		(NOTE: Report re Completion or Rec	sults of multip completion Rep	ple completion on ort and Log form	Well
nent to this work.)* EV:1y Drilling Compar 975. Ran 285 joint: 2,068' with 790 sacl	ny reached total depth s and l cut joint of 7" ks of Class H cement co	OD 26# N-80 LT&C cas ntaining .5% CFR-2.	,069' at sing set WOC 6 ho	8:30 PM, N and cement ours. Temp	and zonem perti larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zonem perti- larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zones perti- larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zones perti- larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zones perti- larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zones perti- larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zonem perti- larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zonem perti- larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zonem perti- larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zones perti- larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zonem perti larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach nrvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zonem perti- larch 16, ed at perature
Nent to this work.)* EV:ty Drilling Compar 075. Ran 285 joints 2,068' with 790 sach urvey indicated top Inutes, OK.	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W /8" hole at 12,069' at	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested	,069' at sing set WOC 6 ho casing w	8:30 PM, N and cement ours. Temp	and zones perti- larch 16, ed at perature 30
nent to this work.)* EV.1y Drilling Compar 175. Ran 285 joints 2,068' with 790 sach invey indicated top inutes, OK. tarted drilling 6-1, 18. I hereby certify that the for	ny reached total depth s and 1 cut joint of 7" ks of Class H cement co of cement at 7490'. W /8" hole at 12,069' at /8" hole at 12,069' at	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested 1:15 PM, March 22, 19	,069' at sing set WOC 6 ho casing w	8:30 PM, M and cement ours. Temp fith 1500#,	24, 1975
Nent to this work.)* EV.1y Drilling Compare D75. Ran 285 joints 2,068' with 790 sach Invey indicated top Inutes, OK. Earted drilling 6-1, 18. I hereby certify that the for SIGNED	ny reached total depth s and 1 cut joint of 7" ks of Class H cement co of cement at 7490'. W /8" hole at 12,069' at /8" hole at 12,069' at State office use)	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested 1:15 PM, March 22, 19	,069' at sing set WOC 6 ho casing w	8:30 PM, M and cement ours. Temp fith 1500#,	24, 1975
18. I hereby certify that the for SIGNED	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W /8" hole at 12,069' at /8" hole at 12,069' at State office use)	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested 1:15 PM, March 22, 19	,069' at sing set WOC 6 ho casing w 975.	ATE March	24, 1975
<pre>ident to this work.)* EV.iy Drilling Compar 075. Ran 285 joints 2,068' with 790 sach invey indicated top inutes, OK. tarted drilling 6-1,  18. I hereby certify that the fo SIGNED</pre>	ny reached total depth s and l cut joint of 7" ks of Class H cement co of cement at 7490'. W /8" hole at 12,069' at /8" hole at 12,069' at State office use)	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested 1:15 PM, March 22, 19	,069' at sing set WOC 6 ho casing w 975.	ATE March	24, 1975
<pre>ident to this work.)* EV.iy Drilling Compar 075. Ran 285 joints 2,068' with 790 sach invey indicated top inutes, OK. tarted drilling 6-1,  18. I hereby certify that the fo SIGNED</pre>	repoing is true and correct State office use) TITLE - TAL, IF ANY:	of 8-3/4" hole at 12, OD 26# N-80 LT&C cas ntaining .5% CFR-2. OC 36 hours. Tested 1:15 PM, March 22, 19	,069' at sing set WOC 6 ho casing w 975.	8:30 PM, M and cement ours. Temp fith 1500#,	24, 1975

•

-1.1

and a second second

. A. **1** 370

( 1. Construction of the C

• • • • •