

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM-2379

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL & 1980' FWL, Section 25, 22-S, 32-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Covington "A" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 25, 22-N, 32-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Due to limited supply of casing in various sizes, we propose the following casing program instead of the one submitted on Form 9-331C, dated December 13, 1974 and approved on January 7, 1975:

Drill 17-1/2" hole to 500' and set 13-3/8" 48# casing and circulate cement. Drill 12-1/4" hole to 5100' and set 9-5/8" 40# casing and bring the top of the cement to the base of the salt section. Drill 8-3/4" hole to 12,200' and set 7" 26# casing and bring the top of the cement to 5000'. Drill 6-1/4" hole to 15,000' and cement 5" liner from approximately 12,000' to 15,000' with 200 sacks of cement.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Area Production Manager

DATE January 10, 1975

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JAN 14 1975

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side