

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name Gill Deep
3. Address of Operator Drawer "D", Monument, New Mexico 88265	9. Well No. 3
4. Location of Well UNIT LETTER N 700 FEET FROM THE South LINE AND 1889 FEET FROM THE West LINE, SECTION 31 TOWNSHIP 21-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat Drinkard
15. Elevation (Show whether DF, RT, GR, etc.) GR 3464'	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Killed well w/75 bbls. water. Perf. 7" csg. w/2 Selectfire Wesjet magnum shots per ft. at 6662' - 64', 66', 68', 6674' - 76', 78', 80', & 82'. Total 8 shots. Runco acidized 7" csg. perfs. fr. 6546' to 6682' w/500 gal. 28% & 5500 gal. 15% NE acid. Used ball sealers. Circ. hole clean to 6710'. Ran 2" x 7" Baker Model R-3 double grip pkr., tbq. & set pkr. at 6504' w/14,000# comp., S.N. at 6503'. Swabbed load. Ran pump & rods, installed pump unit & eng. & resumed prod. as pumping oil well.

Test of 5/11/76: Prod. 30 BO & 20 BW in 24 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED EB Ziskler TITLE Suprv. Adm. Ser. DATE 10/27/80

Orig. Stamp
Leo Carter

APPROVED BY _____ TITLE _____ DATE 10/27/80

CONDITIONS OF APPROVAL, IF ANY: