

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR

CONOCO INC.

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL + 1980' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☒

SHOOT OR ACIDIZE ☒

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) RE PERF, OPEN ADD'L PAY ☒

5. LEASE

LC-031695(B)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

NMFU

8. FARM OR LEASE NAME

WARREN UNIT

9. WELL NO.

41

10. FIELD OR WILDCAT NAME

BLINEBRY / TUBB

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 27, T-20S, R-38E

12. COUNTY OR PARISH

LEA

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
JAN 9 11 25 AM '84
BUREAU OF LAND MANAGEMENT
ROSTER DISTRICT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU. CO TO 6750'. PERF W/ 2 JSPF @ 6530', 33', 36', 38', 50', 52', 55', 58', 62', 81', 93', 96', 6601', 08', 14', 16', 21', 23', 42', + 6645'. SET PKR @ 6050'. ACIDIZE PERFS W/ 95 BBLs 15% HCL-NE-FE, 80 LBS OF 50/50 BENZOIC ACID + ROCKSALT, + GUAR GUM. FLUSH W/ TFW. SWAB. REL PKR. SET RBP @ 6175'. SPOT 9 BBLs 15% ACID 5955'-6175'. PERF W/ 1 JSPF @ 5983', 92', 97', 6004', 08', 13', 18', 25', 6123', 28', 38', 43', 52', 56', 61', + 6165'. SET PKR @ 5970'. PUMP 32 BBLs 15% ACID. FLUSH W/ TFW. FRAC BLINEBRY W/ A TOTAL OF 822 BBLs FRAC FLUID + 67372 LBS 20/40 SAND. FLUSH W/ 60 BBLs TFW. SWAB. REL PKR + RBP. RUN PROD EQUIP. TEST.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John A. Budy TITLE Administrative Supervisor DATE 1/6/84

APPROVED

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAR 21 1984

RECEIVED

MAR 26 1984

O.C.D.
ROBES OFFICE