

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

|   |
|---|
| WELL API NO.<br>30-025-25443  |
| 5. Indicate Type of Lease<br>STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No.<br>V-3551  |
| 7. Lease Name or Unit Agreement Name<br>Northern AKQ State  |
| 8. Well No.<br>1  |
| 9. Pool name or Wildcat<br>Rock Lake Bone Spring  |

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

|   |  |  |  |  |
|---|--|--|--|--|
| 1. Type of Well:<br>OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER RE-ENTRY | 2. Name of Operator<br>YATES PETROLEUM CORPORATION | 3. Address of Operator<br>105 South 4th St., Artesia, NM 88210 | 4. Well Location<br>Unit Letter 0 : 660 Feet From The South Line and 1980 Feet From The East Line<br>Section 28 Township 22S Range 35E NMPM Lea County | 10. Elevation (Show whether DF, RKB, RT, GR, etc.)<br>3524' GR |
|---|--|--|--|--|

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Perforate, Treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Re-entry continued. Squeezed 9-5/8" casing stub at 4430' after using a packer and RBP to determine where casing was leaking. Spot 100 sx Class "C" w/4/10% Halad-3-22, wt 14.4, yield 1.32 + 200 sx Class "C" Neat, wt 14.4, yield 1.32. Squeezed 15 sx into stub @ 2000 psi. Left 72 bbls cement inside 13-3/8" casing. Load annulus - took 4-3/4" bbls. Tag cement @ 4040' Drill cement from 4040-4430'. Tag 9-5/8" casing stub @ 4430'. Test casing to 1000 psi for 10 mins. Drill cement from 4430-4445'. Test casing to 1000 psi for 10 mins. Perforated 6456-6522 w/30 - .42" holes (2 SPF) as follows: 6456, 58, 60, 62, 64, 6480, 84, 86, 89, 95, 6514, 16, 18, 20 and 6522'. Acidize perms 6456-6522' w/1500g. 7 1/2% HCL NEFE acid. Recovered 170 bbls water. Perforated 10 - .42" holes (2 SPF) as follows: 6286, 88, 90, 92 and 6294'. Acidize perms 6286-6294' w/500g. 7 1/2% HCL NEFE acid. Swabbed - recovered no oil or gas. Perforated 10940-10963' w/12 - .42" holes (2 SPF) as follows: 10940, 46, 48, 50, 55 and 10963'. Acidize 10940-10963' w/1000g. 15% HCL NEFE acid. Swabbed - recovered 95 bbls water and 1 bbl oil. Perforate (2 SPF) w/8 - .42" holes as follows: 8472, 74, 76 78'. Acidize 8472-78' w/500g. 7 1/2% HCL NEFE acid.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. /Recovered 60 bbls water with trace of oil./

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-24-92  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE MAR 31  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_