

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Budget Bureau No. 1004-01
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-063458

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Conoco Inc.

3. ADDRESS OF OPERATOR

P.O. Box 460 - Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FSL + 1980' FWL Unit K

14. PERMIT NO.

30-025-25562

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7. UNIT AGREEMENT NAME

Warren Unit

8. FARM OR LEASE NAME

Warren Unit

9. WELL NO.

#46

10. FIELD AND POOL, OR WILDCAT

Blinbury Oil & Gas Warren Unit

Warren Unit Oil Subb. & Blinbury

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

X-946 7

26-205-38E

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1-19-88 Tag fill @ 6745', pull up to 6597' + spot 2 Bbls of 15% HCL-NE-FE acid (inhibit for 48 hrs) Perf. 6557-6560, 6563-6566, 6570-6578, (Total 17 holes). Acidize Tubbs perfs w/57 Bbls of 15% HCL-NE-FE acid (inhibit 24 hrs.) Acidize Blinbury perfs w/38 Bbls of 15% HCL-FE + 2 Bbls (84 gals) Checker Set Chemically inhibit Blinbury + Tubbs perfs w/2 drums SP-307, 1 gal RP-2336 in 20 Bbls of 2% KCL water + 1/2 gal ODS-980. Run prod. equip.
Work completed 1-26-88

18. I hereby certify that the foregoing is true and correct

SIGNED W.W. Baker W.W. Baker

TITLE Administrative Sup'v

DATE Aug. 25, 1989

(This space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS TITLE

CONDITIONS OF APPROVAL, IF ANY

DATE

CARMAID-100-10000*See Instructions on Reverse Side