

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name <u>Central Drinkard Unit</u>
2. Name of Operator <u>Gulf Oil Corporation</u>	8. Farm or Lease Name <u>C</u>
3. Address of Operator <u>P. O. Box 670, Hobbs, NM 88240</u>	9. Well No. <u>421</u>
4. Location of Well UNIT LETTER <u>A</u> <u>BHL 1274</u> FEET FROM THE <u>North</u> LINE AND <u>1250</u> FEET FROM THE <u>East</u> LINE, SECTION <u>32</u> TOWNSHIP <u>21S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat <u>Drinkard</u>
15. Elevation (Show whether DF, RT, GR, etc.) <u>3451' GL</u>	12. County <u>Lea</u>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
OTHER <u>Sz perfs, recompleting lower Drinkard</u> <input checked="" type="checkbox"/>		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

POH with production equipment. Set cement retainer at 6300'. Squeeze 6348'-6420' with 150 sacks Class "C" with Halad-4 and CFR-2. Drill up cement retainer and cement; clean out to 6716'. Test squeezed perfs. Perf 6540-44', 6561-65', 6582-86', 6608-12' with (2) 1/2" burrless JHPF (32 holes). Spot 15% NEFE HCL 6612'-6500'. Acidize with 2400 gals 15% NEFE slick HCL and (36) 7/8" RCNB'S. Frac with 36,000 gals pad, 58,000# 20/40 sand and (24) 7/8" RCNB'S. Swab and test.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED RD Pate TITLE Area Engineer DATE 8-7-81

APPROVED BY Jerry S. Smith TITLE Area Engineer DATE AUG 10 1981

CONDITIONS OF APPROVAL, IF ANY: