

Della Boren # 4 Procedure
Page Three

*Fluid Composition: Additives per 1000 gals

2000 gal pre-pad (50% CO₂)

30 gal Papasperse
10 gal Paracheck 140
1 gal Losurf-259
166 lbs. KCL
10 lbs. WG-11

5000 gal Pad (50% CO₂)

1 gal Lo surf-259
40 lbs. Adomite Aqua
50 lbs. WG-11
10 lbs. CW-1
166 lbs. KCL
1 lbs. GBW-3
30 gal. PROTEX-ALL

15,000 gal. frac (50% CO₂)

1 gal Losurf-259
40 lbs. Adomite Aqua
50 lbs. WG-11
10 lbs. CW-1
166 lbs. KCL
1 lb. GBW-3

500 gal flush (50% CO₂)

1 gal. Losurf-259
166 lbs. KCL
10 lbs. WG-11

Rates

CO₂ at 7.5 BPM
Liquid at 7.5 BPM
Total CO₂- 55 tons

Shut in well 1 hr., then flow back. Swab if necessary.
POH w/ pkr. and WS.
GIH w/ hydrostatic bailer and cleanout sand to 3979'.
GIH w/ 2-3/8" tbg., 3/4" rods, and 1½" pump. Set SN at 3700'. TS at 3731'.
Bean well and test.

RECEIVED

JUN 17 1982

O.C.D.
HOBBS OFFICE