

# COPY TO O. C. C.

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

### SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well    gas ☐ well    other ☐
2. NAME OF OPERATOR  
CONTINENTAL OIL COMPANY
3. ADDRESS OF OPERATOR  
P.O. Box 460 Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL & 1650' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: SAME
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON\* ☐
- (other) SET SURF. CSG

SUBSEQUENT REPORT OF:

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☒

5. LEASE  
LC 031670(b)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
WARREN UNIT
8. FARM OR LEASE NAME  
WARREN UNIT
9. WELL NO.  
50
10. FIELD OR WILDCAT NAME  
WARREN BLINERY-TUBB
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SEC. 29, T. 20S, R. 38E
12. COUNTY OR PARISH  
LEO
13. STATE  
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3542.7' GR.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)\*

9-3. MIRD. Spud @ 4:00 PM.

9-4 PRESENT DEPTH 1390', SURFACE CSG POINT. PROG 390'. CIRC HOLE. RU CASERS. RUN CSG AS FOLLOWS: RAN 9-5/8" GUIDE SHOE, 35' SHOE JT, FC & 33 JTS 9-5/8", 36#, K-55, LT&C CSG. TOTAL PIPE 1392', PIPE TO KB 1390', PIPE TO GL 1379'. RU HOWCO, CMT AS FOLLOWS: PUMP 250 SKS CLASS "C" CMT, 4% GEL & 2% CA CL2. FOLLOW W/300 SKS CLASS "C", 2% CA CL2. DROP PLUG & DISPLACE TO FC W/104 BBLs FRESH WTR. BUMP PLUG AT 10:45 PM. CIRC 75 SKS TO SURFACE. WAITING ON CMT.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm. A. Butterfield TITLE ADMINISTRATIVE SUPERV. DATE 9-6-78

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

46G5 [5], NMF4 [4], FILE

\*See Instructions on Reverse Side

