

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Continental Oil Company

3. ADDRESS OF OPERATOR
Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: *2030' FNL + 1980' FWL*
AT TOP PROD. INTERVAL: *Same*
AT TOTAL DEPTH: *Same*

5. LEASE
LC-063458

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
WARREN

8. FARM OR LEASE NAME
WARREN UNIT

9. WELL NO.
48

10. FIELD OR WILDCAT NAME
Warren, Blinobry-Tubb

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 26, T. 20S, R. 38E

12. COUNTY OR PARISH
Lea

13. STATE
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3558.6 GR

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <i>Set 9 3/8" Surface CSG</i> <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 7-7-78 and drilled to 1562'. Ran 9 3/8" 36 lb K-55 CSG set at 1562'. Cmt'd w/ 650 SX of class 'C' cmt. Plug down at 11:25 PM 7-8-78. Testbed CSG to 300 PSI, Hold ok. Drilled ahead with 8 3/4" hole. Circ 45 SX CMT

RECEIVED

JUL 12 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO
Set @ _____ Ft.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED *W. A. [unclear]* TITLE *Admin. Supv.* DATE *7-11-78*

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY: _____

ACCEPTED FOR RECORD
DATE JUL 12 1978
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

RECEIVED

JUL 18 1978

OFFICE OF THE ATTORNEY GENERAL
PROSECUTOR GENERAL
ALBANY, N. Y.