Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☑   gas well ☐   other

2. NAME OF OPERATOR
CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 1980' FEL.
AT TOP PROD. INTERVAL: —
AT TOTAL DEPTH: —

5. LEASE
LC 063458

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Warren Unit

8. FARM OR LEASE NAME
Warren Unit

9. WELL NO.
55

10. FIELD OR WILDCAT NAME
Blinebry + Tubb

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 26   t 20 N R 38 E

12. COUNTY OR PARISH
Lea

13. STATE
N. M

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3561.5' GR

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐   ☐
FRACTURE TREAT ☐   ☐
SHOOT OR ACIDIZE ☐   ☐
REPAIR WELL ☐   ☐
PULL OR ALTER CASING ☐   ☐
MULTIPLE COMPLETE ☐   ☐
CHANGE ZONES ☐   ☐
ABANDON* ☐   ☐
(other) set 7" prod. csg.

RECEIVED
JAN 2 1979
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

(NOTE Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-25-78 reached TD of 6900' @ 10:00 AM. circ. 2 hrs., log.

12-27 ran 7" FS, 38' SJ., 7" rc & 24 jts 7", 26#, K-55, LT&C, 41 jts

7", 23#, K-55, LT&C, DV tool, 90 jts 7", 23#, K-55, LT&C

total 156 jts. set csg @ 6900' KB, DV tool @ 3985' KB

cmt w/ 650 sx in first stage (class C cmt). disp w/ 113 bbls KCL wtr & 157 bbls drlg mud
circ 50 sx off DV tool.

2nd stage - 1600 sx Lite cmt - circ 250 sx to surf. rd'l rig

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _Wm A. Rutherford_   TITLE _Admin Supv_   DATE _12-27-78_

(This space for Federal or State office use)

APPROVED BY _____   TITLE _____   DATE _____
CONDITIONS OF APPROVAL, IF ANY:

4565   5
NMFU   4
File

ACCEPTED FOR RECORD
JAN 2 1979
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side