	n 9–331 y 1963) DEP	UNI D STATES ARTMEN: OF THE INTE GEOLOGICAL SURVEY		Entros Entros	u No. 42-R1424.
	SUNDRY (Do not use this form fo Use "A	NOTICES AND REPORT r proposals to drill or to deepen or pl PPLICATION FOR PERMIT—" for su	S ON WELLS lug back to a different reservoir, ich proposals.)	6. IF INDIAN, ALLOTTER	OR TEIBE NAME
	OIL XX GAS OTHER			7. UNIT AGREEMENT NAME	
2.	AME OF OPERATOR			8. FARM OR LEASE NAM	(E
	Adobe Oil & Gas C	Llano Federal			
3.	ADDRESS OF OPERATOR	9. WELL NO.			
	1100 Western Unit	1 1			
4.	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*			10. FIELD AND POOL, OR WILDCAT	
	See also space 17 below.) At surface	Blinebry-Warren (Tubb)			
	660 FSL & 660 FWI	L		11. SEC. T., R., M., OR BLK. AND SUBVEY OR ABEA SEC. 23, T-20-S, R38E	
14.	PERMIT NO.	15. ELEVATIONS (Show whethe	er DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE
		3562.5 GR		Lea	NM
16.	Che	eck Appropriate Box To Indicat	te Nature of Notice, Report, or (Other Data	
	NOTICE 0	ENT REPORT OF:			
	TEST WATER SHUT-OFF	FULL OR ALTER CASING	WATER SHUT-OFF	BEPAIRING V	VELL
	FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA	SING
	SHOOT OR ACIDIZE	ABANDON* X	SHOOTING OR ACIDIZING	ABANDONME	T*
	REPAIR WELL	CHANGE PLANS	(Other)		
	(Other)			s of multiple completion letion Report and Log for	
17.	DESCRIBE PROPOSED OR COMPLE proposed work. If well is nent to this work.) *	TED OPERATIONS (Clearly state all pert directionally drilled, give subsurface	inent details, and give pertinent dates locations and measured and true vertic	, including estimated dat	e of starting any

Spud 12-1/4" hole @ 6;15 p.m. 2/20/78. Drld 12-1/4" hole to 1620' and ran 38 jts of 9-5/8" 40#/ft & 36#/ft. Set @ 1566' & cemented w/600 sx Class "C" 50/50 pozmix w/2%CaCl w/6# Gilsonite/sx + 200 sx Class "C" w/2% CaCl. Cement circ. POB 11:30 a.m. 2/22/78. Tested csg to 1000# for 30 min & tested BOP to 1000#, held ok.

Excessive deviation in the hole was determined after drilling to 3222' & it was decided to P&A the hole. We plan to plug the hole as follows: 120 sx Class "C" w/2% CaCl from 2700'-3000'

Wireline BP @ 1550' w/50 sx Class "C" w/2% CaCl from 1550'-1450' 15 sx Class "C" w/2% CaCl from 45'-surface.

Plan to skid rig 63' east & start replacement well, Llano Federal #1-Y.

I hereby certify that the foregoing is true and SIGNED		Dist. Prod. Mgr.	DATE 2/25/78
(This space for Federal or State office use)			VFD
APPROVED BY CONDITIONS OF APPROVAL, IF ANY :	TITLE	APBRO	
	*See Instruct	ions on Reverse Side FRAUR R.	BROWN
		DISTRIC	- -