

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-031736 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gillully B Federal

9. WELL NO.

17

10. FIELD AND POOL, OR WILDCAT

Monument - Tubb

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

21-20-37

12. COUNTY OR PARISH

Lea

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Drawer A, Levelland, TX 79336

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL X 1650' FEL (Unit B, Sec.21)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3522.1 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

Spud ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Rod Ric Drilling Co. (Rig No. 8) spudded a 17½" hole on 3/4/78. Reached TD of 1206' 3/7/78. Ran 13-3/8" 48# H-40 ST&C casing and set at 1206'. Cemented with 600 sx Econolite and 150 sx Class C w/2% CACL. Plugged down 11:15 A.M. 3/7/78. Circulated 75 sx. WOC 18 hrs. Test casing with 800# for 30 minutes. Test ok.

Reduce hole to 12-1/4" and resumed drilling 10:30 P.M. 3/8/78.

RECEIVED

FEB 13 1978

U. S. GEOLOGICAL SURVEY
HOBBES, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Randy Atkins

TITLE Asst. Administrative Analyst DATE 3-10-78

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

0 & 4 - USGS-H

1 - Div.

1 - Susp.

1 - RC

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAR 13 1978

U. S. GEOLOGICAL SURVEY
HOBBES, NEW MEXICO