

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

NM 17252 15272

6. IF INDIAN ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL OR WILDCAT

11. SEC., T., R., M., OR BLK. AND

12. COUNTY OR PARISH

13. STATE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT ON:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Drilg operations

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths from all markers and zones pertinent to this work.)\*

Spudded 4:30 p.m. 2/26/78. Drld to 1572'. Ran 41 jts 9-5/8" 36# K-55 csg 1593'. Set @ 1572' Cemented w/600 sx Class "C" 50/50 pozmix w/2% gel w/6# Gilsonite w/2% CaCl + 200 sx Class "C" w/2% CaCl. Circ 200 sx cement to pit. Tested BOP, would not hold. Repaired BOP & tested to 1000#, ok. Drld to 6855' T.D. Ran 187 jts 7" 35# Secondary 70 csg 6842'. Set @ 6855'. Cemented w/400 sx Halliburton Lt. Wt. w/10# salt/sx w/1/4# flocele/sx + 500 sx Class "C" w/ 5# salt/sx w/1/4# flocele/sx w/1-10% CFR-2. Ran temp survey, found top of cement @ 2580'. Perforated Tubbs w/1 hole @ 6595, 6610, 14, 18, 31, 37, 48, 64, 67, 70, 95, 6700, 20, 24' (14 holes). Spotted 6 BA across perfs 6595-6724'. Pulled pkr to 6452' & set. Treated perfs w/3000 gal 15% DS-30 acid. Swabbed & flowed 70 bbls. Last run w/swab, fluid cut 50% oil. Spotted 1000 gal DS-30 acid. Fraced perfs w/60,000 gal gelled KCl water w/80,000# 20-40 sand. WIH w/RTTS pkr & set @ 6452'. Swabbed. Perforated Blinberry @ 5920, 29, 30, 41, 46, 51, 53, 6052, 55, 65, 6143, 70, 75, 77' (14 holes). GIH w/RBP & pkr. Set RBP @ 6450'. Dumped 10 sx sand on top of BP.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Dist. Prod. Mgr.

DATE 4/7/78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

APR 10 1978

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side

RECEIVED

APR 11 1978

OIL CONSERVATION COMMISSION  
WASHINGTON, D. C.