

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR  
*Continental Oil Company*
3. ADDRESS OF OPERATOR  
*P.O. Box 160 Hobbs, N.M. 88240*
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: *660' FNL & 1980' GWS*  
AT TOP PROD. INTERVAL: *-*  
AT TOTAL DEPTH: *-*
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON\* ☐
- (other) *set 9 5/8" string casing* ☒

## SUBSEQUENT REPORT OF:

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

## 5. LEASE

*LC - 063458*

## 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## 7. UNIT AGREEMENT NAME

*N.M. 121*

## 8. FARM OR LEASE NAME

*Warren Unit*

## 9. WELL NO.

*53*

## 10. FIELD OR WILDCAT NAME

*Blinney & Sub*

## 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

*Sec 26, T-20S, R-38E*

## 12. COUNTY OR PARISH

*Lea*

## 13. STATE

*N.M.*

## 14. API NO.

## 15. ELEVATIONS (SHOW DF, KDB, AND WD)

*3561.5' GR*

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OCT 30 1978

U. S. GEOLOGICAL SURVEY

HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

*10-23-78 spud well. Drill 12 1/4" hole to 1560' KB.**10-24 rig up casing, run grade shoe. 45' shoe ft, float collar. 3 1/2" to 9 5/8", 36" K-55 STC. Set @ 1560' KB, 1549' 6L. Cmt. as follows:*

CIRC HOLE. RU TO CMT. FMPD 400 SKS CLASS "C" CMT W/2% CA CL, 4% CEL MIXED AT 10.3#/GAL. TAILED IN W/200 SKS CLASS "C" CMT W/2% CA CL MIXED AT 14.8#/GAL. CIRC 74 SKS CMT. PLUG DOWN AT 8:00 AM. WOC.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Wm. A. Butterfield*

TITLE

*Cemin Supr.*

DATE

*10-26-78*

(This space for Federal or State use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

*USGS 5*  
*NMTH 4*  
*FILE*

\*See Instructions on Reverse Side

