

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Continental Oil Company
3. ADDRESS OF OPERATOR
P.O. Box 460, Hobbs N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: *660' FNL & 1980' FCL*
AT TOP PROD. INTERVAL: -
AT TOTAL DEPTH: -

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) *change well number*

5. LEASE

LC 063458

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

N.M. J. 26

8. FARM OR LEASE NAME

Warren Unit

9. WELL NO.

56

10. FIELD OR WILDCAT NAME

Blindly - Sub

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T-20S, R-38E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3562.5' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to change the number of this well from 57 to 56. This change will reflect an order of drilling. This location was approved 4-27-78 as Warren Unit No. 57.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. A. Dutterford

TITLE

Admin. Supr.

DATE

10-16-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

4565 (5)

NMFH (4)

FILE

*See Instructions on Reverse Side

