

Form 3-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-031737 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. NAME OF OPERATOR Amoco Production Company	
3. ADDRESS OF OPERATOR P.O. Drawer A, Levelland, Texas 79336	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1930' FNL & 760' FEL (Unit H, Sec 21)	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3513.5 GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gillully B Federal

9. WELL NO.

20

10. FIELD AND POOL, OR WILDCAT

Cass Penn

11. SEC., T., R., M., OR BLE. AND
SURVEY OR AREA

21-20-37

12. COUNTY OR PARISH

Lea

13. STATE

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spud ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 5-16-78 Capitan Drilling Co. (Rig #16) spudded a 17 1/2" hole at 8:30 PM. Drilled to TD of 1204' and set 13 3/8" 48# H-40 ST&C casing at 1204'. Cemented with 600 sacks LO dense and 150 sacks Class C. Circulated 75 sacks. Plug down at 1:00 PM 5-19-78. WOC 25 hrs. Test casing with 1000# for 30 minutes. OK. Reduced hole to 12 1/4" and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. V. Healey

TITLE Administrative Analyst

DATE 5-26-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

0+4-USGS-H 1-Div 1-Susp 1-AVH

TITLE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAY 30 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

000000 000 000000

RECEIVED

JUN 06 1978

OIL CONSERVATION COMM.
HOBBS, N. M.