

SURFACE INFORMATION

[illegible]

Cushion Type	Amount	Pressure	Bottom Choke
	—		Size 5/8"

MUD DATA

Mud Type	FRESH WATER GEL	Wt.	8.8	
Viscosity	32	Water Loss	21.0	C.C.
Resist: of Mud	1.6 @ 88 °F;	of Filtrate	1.6 @ 88 °F	
Chloride Content	2000			PPM

EQUIPMENT & HOLE DATA

Type Test	M.F.E. OPEN HOLE		
Formation Tested	STRAWN		
Elevation			Ft.
Net Productive Interval	10		Ft.
Estimated Porosity	10		%
All Depths Measured From	KELLY BUSHING		
Total Depth	9464		Ft.
Main Hole/Casing Size	8 3/4"		
Rat Hole/Liner Size	-		
Drill Collar Length	352'	I.D.	2.25"
Drill Pipe Length	8985'	I.D.	3.80"
Packer Depth(s)	9371 & 9375		Ft.

MULTI-FLOW EVALUATOR FLUID SAMPLE DATA

Sampler Pressure	0	P.S.I.G. at Surface
Recovery: Cu. Ft. Gas	.27	
cc. Oil	-	
cc. Water	-	
cc. Mud	1710 (OIL & GAS CUT)	
Tot. Liquid cc.	1710	
Gravity	-	°API @ - °F.
Gas/Oil Ratio	-	cu. ft./bbl.

RESISTIVITY	CHLORIDE CONTENT
-------------	------------------

Recovery Water	—	@	—	°F.	—	ppm
Recovery Mud	—	@	—	°F.		
Recovery Mud Filtrate	—	@	—	°F.	—	ppm
Mud Pit Sample	1.6	@	88	°F.		
Mud Pit Sample Filtrate	1.6	@	88	°F.	2000	ppm

[illegible]

Remarks: _____

Address P.O. BOX 1710; HOBBS, NEW MEXICO 88240

Company ATLANTIC RICHFIELD COMPANY Field WILD CAT (BELL LAKE)
Well LANGLEY GETTY COM. #1 Location SEC. 21 - T22 - R36E

Well _____
Test Interval 9375' TO 9464' Test # 2 Date 7-20-78

County LEA State NEW MEXICO Field Report No. 06051 D
 Technician HART (HOBBS) Test Approved By MR. D.D. MCDANIEL No. Reports Requested 5 (3X'S)