## COPY 71 D. C. C.

Form 9–331 Dec. 1973	Form Approved. Budget Bureau No. 42R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	LC 031695 (B)
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a differen reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas well well other	9. WELL NO.
	52
Continental Oil Company	10. FIELD OR WILDCAT NAME
Continental Oil Company 3. ADDRESS OF OPERATOR PO. Box 460 Hobus, MM 88240	Blinchry, Juber 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Suc. 29 J-205, R-38E
below.) AT SURFACE: 23/0'952 & 330'FE2	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: 🛏	dea mm
AT TOTAL DEPTH:	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	35-2719'6R
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
FRACTURE TREAT	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE	
ABANDON*	
(other) SET 7 prod cog X	
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly st including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertin</li> <li>DEL D TO 6783 * TD AT 2: 10 145 * CIR TRI PPING OUT TO LOG.</li> <li>RU SCHLUMBERGER &amp; RUN GR-DNL, FDC &amp; 6733 * 2600 * RAY CALIPER FROM TD TO TD TO 4300 * WIH M/DS &amp; CIRC HOLE RAY FS, 33 * 7" OD, 26# SJ, FC 13 JT 53 JTS 7" OD, 23#, K-55, LT&amp;C, DU TO 23#, K-55, LT&amp;C CSG. TOTAL 174 JTS 6777 * GL, W/FC AT 6755 * KB, 6744 * G 3939 * GL. CIRC CSG DD WY. (over)</li> </ol>	directionally drilled, give subsurface locations and ent to this work.)* C HOLE 2 HES. DLL LOGS FROM TD D 1332 * RAN MSFL FROM 1-1/2 HES. RU CASERS & S 7" OD, 26# K-55, LT&C OOL & 102 JTS 7" OD, , CSG SET AT 6733 * KE,
Subsurface Safety Valve: Manu, and Type <b>18.</b> Thereby certify that the foregoing is true and correct SIGNED TITLE Comm. Su	Set @ Ft.
(This space for Federal or State	office use)
APPROVED BY	DAJE
PESTAS J	TED FOR RECORD
gile *See Instructions on Revers	DET 25 1978 (1)
see instructions on Revers	TRUCT NO CONTRACTOR
h1. S. C	GEOLOGICAL SURVEY

State or Federal office for specific instruction Item 17: Proposals to abandon a well addition, such proposals and reports single off by cement or above plugs; amount, size, method of part conditioned for final inspection looking to a Indian lands pursuant to applicable Federa regulations. Any necessary special instruct procedures and practices, either are shown

General: This form is designed for su

PUMP 10-23 RU DOWELL, CAT AS FOLLOWS: IST STACE. 10 BBL S F SPACER FOLLOW W/265 SKS CLASS "C" C:1 T. 4% GEL 3#/ SK SAL T FOLLOW 13 BELS "C" SL UEEY, W/ 325 SKS CLASS C:4 T W/3#/SK SAL T. L EAD DISPLACE W/103 TFU 8 1 59 BBL S BUMP PLUG FU. TO 2 50 0 A4, RATE AT 3:30 €. 5 PSI. **PLUG** DO WN BP1. DEO P FREE FALL AT 9:00 CIRC 5 SKS PL UG 8 0 P EV DV TOOL AM. 50 SKS 0 FF DV TOOL. 2ND ST S TFW. STAGE LITE E - 1235 BLMP PLUG CIRC *2*‡ HRS. PUMP C:1 T 13% SAL T. 2000 TO S PLUG TO 135 SKS DISPLACE W/159 BELS PSI. FLUG DOWN SKS TO SURFACE. Release rig at s EATE 7 CIEC SET BPM. AT 2: 30 P.1. CSG. 5:00 SLIPS, NIPPLE DOWN, CUT OFF AM, 10-22-73.

•

.

. .

Instructions

rtain well operations, and reports of such operations when completed, as indicated, on Federal and proved or accepted by any State, on all lands in such State, pursuant to applicable State law and the number of copies to be submitted, particularly with regard to local, area, or regional in the number of copies to be submitted. y be obtained from, the local Federal and/or State office.

eral or Indian land should be described in accordance with Federal requirements. Consult local

ndonment; data on any former or present productive zones, or other zones with present significant n) and method of placement of cement plugs; mud or other material placed below, between and onment should include such special information as is required by local Federal and/or State offices pulled and the depth to top of any left in the hole; method of closing top of well; and date well site

VERNMENT PRINTING OFFICE : 1974-0-533-007