

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐2. NAME OF OPERATOR  
Amoco Production Company3. ADDRESS OF OPERATOR  
P.O. Drawer "A", Levelland, Texas 793364. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2310' FNL & 1980 FNL, Sec 33 (Unit F)  
AT TOP PROD. INTERVAL: SE $\frac{1}{2}$ , NW $\frac{1}{2}$   
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) Set casing &amp; test

## SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED

FEB 1 1979

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO5. LEASE  
LC-031736-b

6. IF INDIAN, ALIOTTE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Gillully "B" Federal9. WELL NO.  
2210. FIELD OR WILDCAT NAME  
Wildcat-Grayburg

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

33-20-37

12. COUNTY OR PARISH  
Lea13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3553.4 RDB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Abandoned the Drinakrd zone by spotting a 60 sx Class H cement plug 7110'-6960'. Spotted a 60 sx Class H cement plug 6615'-6465'. Spotted a 75 sx. Class H cement plug 5325'-5175'.

Ran 5 1/2" 17#, 14#, 15.5# K-55 ST &amp; C casing and set at 4200'. Cemented with 1210 sx plus additives. PD 9:45 a.m. Estimated top of cement at 2225' by temperature survey. Released rig 1:00 P.M. 1/10/79. Casing will be tested when service unit is moved on the well.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray Cox

TITLE

Admin. Supervisor

DATE

January 29, 1979

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

0+4-USGS-H  
1-Houston  
1-Susp  
1-DE

TITLE

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

FEB 1 1979

J. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO