

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
P.O. Drawer "A", Levelland, Texas 79336
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310' FNL & 1980' FWL, Sec 33 (Unit F,
AT TOP PROD. INTERVAL: SE $\frac{1}{4}$, NW $\frac{1}{4}$)
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☒
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

JAN 17 1979

**U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO**

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to TD 7200' and evaluated well. Propose to abandon Drinkard and test the Grayburg and Queen. Spot 60 sx Class H cement plug 7110'-6960'. Spot 60 sx Class H cement plug 6615'-6465'. Spot 75 sx Class H cement plug 6070'-5920'. Spot 75 sx Class H cement plug 5325'-5175'. This procedure received verbal approval on 1/9/79 per Mr. A.R. Brown.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray Cox TITLE Admin. Supv. DATE January 12, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

0+4-USGS-H
1-Houston
1-Susp
1-DE

*See Instructions on Reverse Side

