

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL / 330' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
LC031670 b

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
SEM4

8. FARM OR LEASE NAME
SEM4 BLINBRY

9. WELL NO.
101

10. FIELD OR WILDCAT NAME
Blinbry + Tubb

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 29 T. 20S R. 30E

12. COUNTY OR PARISH
LEA

13. STATE
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3527.1' GR

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	☐	☐
FRACTURE TREAT	☐	☐
SHOOT OR ACIDIZE	☐	☐
REPAIR WELL	☐	☐
PULL OR ALTER CASING	☐	☐
MULTIPLE COMPLETE	☐	☐
CHANGE ZONES	☐	☐
ABANDON*	☐	☐
(other) set 7" prod csg	☒	☒

RECEIVED

MAR 30 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

(Note: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-19 Drilled to 6758' TD. circ hole, prep to log.

3-22 Ran 7" csg as follows:

FS, SJ, FC, 95' to 26", ECP, 5' to 26", ECP, 1' to 26", DV tool,
61' to 26" (TOTAL 163' jts) set @ 6738' KB, 6727' GL.

FC @ 6697' KB
ECP @ 25274' KB = 2534' KB
DV TOOL @ 2484' KB
CMT. 1st stage as follows:
450sx Class Cement + addit.
400sx
open DV tool.
ECP. not holding.

3-23 circ. DV tool 11 hrs. while waiting on orders.
Close DV tool, set slips, nipple dn. Bal. rig.
leave well plug thru csg - csg Annulus.

3-24 W.O. completion

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John A. Butterfield TITLE _____ DATE 3-29-79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

U56-6 5
NMFU 4
File

*See Instructions on Reverse Side

ACCEPTED FOR RECORD
MAR 30 1979
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

U.S. Y50

RECEIVED
FEB 11 1960
U.S. DEPARTMENT OF AGRICULTURE
WASHINGTON, D.C.

APR 1960
OIL CONSERVATION COM. 11
FED. RES. B.