

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
1	35' class 6 creosoted pine pole				
2	3 1/2" x 4 1/2" x 8' treated crossarm				
3	1/2" x 5" porcelain pin insulator		463		
4	5/8" x 5" forged steel pin w/sq. washer, nut, & locknut	881			
5	3/4" x 12" machine bolt w/ nut (or length req'd)	881/2			
6	2 1/4" x 2 1/4" x 3/16" x 11/16" hole sq. washer	681/3			
7	5/4" x 1" locknut	351/2			
8	1/4" x 1 1/4" x 28" flat crossarm brace	712/3			
9	1/2" x 4" F7 Felter Drive Log Screw	508754			
10	3/8" x 4 1/2" carriage Bolt w/ Nut	8634 1/2			
11	3/8" x 4" locknut	3510			
12	Preformed Aluminum Alloy Armor Rods, size req'd				
13	1/4" wire #5 strong alum. alloy			KEARNEY #32102560	X
14	Heavy Insulator (Extension Lin'g)				
15	35' class 5 creosoted pine pole			KEARNEY SERIES "B1"	X
16	Aluminum double tab Squeeze on Connector				
17	for A-5R, Aluminum, or Copper-size req'd	66200			
18	6" Suspension Insulator	6502			
19	5/8" standard oval eye Nut		14050		
20	Primary Load and Clamp				
21	5/8" x 18" (or length req'd) Double Arming Bolt	8860			
22	w/4 sq. nuts				
23	Full size detail - see dwg No. ES-10 for specs.				
24	Hot Line Clamp	5152046P		KEARNEY	
25	Squeeze on basket, size required				X

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CCNCCO HOBS DIVISION	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB: ELEC SPECS	DRAWING NO: ES-1
		SHEET 1 OF 3	