

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
a	double unset bolt s/sq. nut, round washer, and corner key on short end, sq. nut and NF locknut on long end, 15 1/8" long (or length required.)	7828			
b	let process porcelain secondary spool insulator, 3" brown glaze		U/OI		
d	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. DWG ES-1B note: provide clamp and ground conduit parallel groove clamp, size req'd			BURNBY SERIES "UC"	
e	secondary insulator clevis for 4" insulator				
f	5/8" thimbleye nut	6510			
h	5/8" x 12" (or length req'd) straight thimbleye bolt w/sq. nut	5512			
j	transformer cluster mount bracket (small)			ALUMAFORM 6M3-6	X
l	transformer cluster mount bracket (large)			ALUMAFORM 15M3-6	X
m	req'd size raintight disconnect & fuses, 3-phase, 600 V. Ref. DWG. No. ES-1B				
n	16" cross plate anchor (or size req'd)	X-16			
q	8-way expanding anchor (size req'd)	88135			
t	4" brown glaze wet process porcelain secondary spool insulator		JO/OI		
u	5/8" x 7' thimbleye anchor rod w/nut (use twineye if req'd - Change No. 5347)	5317 (NUT 55006P)			
at	3/4" high strength guy strand (10,800 lb.)				
bt	prepared guy grip for 3/8" guy strand				
dl	5/8" x 16" angle thimbleye bolt w/nut	5010			
ee	3"x3"x1/4"x11/16" hole curved washer	6823 1/2			X
ff	6" - guy clamp w/3-1/2" bolts				
re	rolling size strain insulator				
hh	service sleeve for 3/8" guy strand	6454			
jl	3/16" x 2-1/2" x 7" lift plate	7887			X
na	pole bottom ground plate (may use butt-wrap if desired)				
og	(ground connection (See DWG. ES-12)				
tr	wet process porcelain secondary spool insulator, 3" - white glaze				
tt	wet process porcelain secondary spool insulator, 4" - white glaze				

DATE:	12-27-71	TITLE:	
DRAWN BY:	E. WINTER	DESCRIPTION MATERIALS	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE:	NONE		

PRODUCTION DEPT.	HOBBS DIVISION
JOB:	DRAWING NO.:
ELEC SPECS	ES-1
	SHEET 3 OF 3