

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL + 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☒
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☒
(other) INHIBIT ☒

5. LEASE
LC-063458
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
NMFU
8. FARM OR LEASE NAME
WARREN UNIT Bl. Bty. 14
9. WELL NO.
57 Warren Unit Subb
10. FIELD OR WILDCAT NAME
BLINEBRY / TUBB
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 26, T-20S, R-38E
12. COUNTY OR PARISH
LEA
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
DEC 28 10 16 AM '83

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 9/2/83. Pmpd 700 GALS XYLENE 6300'-6726'. FLUSHED W/23 BBLs TFW. SPOTTED 3 BBLs 15% ACID 6660'-6726'. PERF W/1 JSPF @ 6660', 66', 76', 82', 86', 96', 99', 6703', 11', 14', 19', 21', + 6726'. SET PKR @ 6249'. ACIDIZED PERFS W/104 BBLs PAD ACID. FLUSHED W/40 BBLs TFW. SWBD. INHIBITED W/1 DRUM CHEMICAL IN 26 BBLs TFW. FLUSHED W/118 BBLs TFW. REL PKR. SPOTTED 11 BBLs 15% ACID 5933'-6198'. PERF W/1 JSPF @ 5933', 41', 55', 65', 98', 6004', 09', 15', 24', 74', 78', 84', 6100', 46', 54', 67', 70', 86', 93', + 6198'. Pmpd 500 GALS XYLENE OVER PERFS. ACIDIZED PERFS W/160 BBLs PAD ACID. FLUSHED W/40 BBLs TFW. SWBD. INHIBITED W/1 DRUM CHEMICAL IN 26 BBLs TFW. FLUSHED W/216 BBLs TFW.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Peter W. Chester TITLE Administrative Supervisor DATE 12/28/83

PETER W. CHESTER

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL IF ANY:

RECEIVED

MAR 7 1984

S.C.D.
HOMES OFFICE

WARREN UNIT No. 57

REL PKR + RBP. RAN PRODUCTION EQUIPMENT.
TUBB PMPD 6 BO, 17 BW, + 5 MCF IN 24
HRS 10/31/83. BLINBRY PMPD 23 BO, 53 BW,
+ 144 MCF IN 24 HRS 10/8/83.