

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR  
CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR  
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL and 660' FNL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) set prod esg.

5. LEASE  
LC 063458

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
NMFU

8. FARM OR LEASE NAME  
Warren Unit

9. WELL NO.  
57

10. FIELD OR WILDCAT NAME  
Warren Blending + Tub

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SEC. 26, T20S, R-38W

12. COUNTY OR PARISH  
Lea

13. STATE  
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3559.5' GR

RECEIVED

FEB 27 1979

(NOTE: Report results of multiple completion or zone completion on Form 9-331-C)

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

drld to 6820' TD 2-17-79 and ran logs. Raw esg @ follows:

FS, 41' SS, FC, 25 jts 7" 26" K-55, LT; c, 43 jts 7", 23", K-55, LT; c

stage collar + 99 jts 7", 23", K-55, LT; c set @ 6809' GL w/

stage collar @ 4017' KB (4006' GL) cmt'd as follows: 550 sk Class Ccmt.

circ 75 sk off DV tool. Pmpd 1300 sk BJ Ltr cmt in 2<sup>ND</sup> stage, circ 200 sk to surf.

W.O.C. 18 hrs - press test to 1000 psi for 15 mins. held O.K.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John A. Duckert TITLE Admin Supr DATE 2-21-79

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

USGS 5  
NMFU 4  
File.

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD  
FEB 26 1979  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO