

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
CONTINENTAL OIL COMPANY
3. ADDRESS OF OPERATOR
P. O. BOX 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' 372 + 660' 422
AT TOP PROD. INTERVAL: -
AT TOTAL DEPTH: -

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) SET SURF CSG.

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☒

RECEIVED

FEB 3 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 12 1/4" hole @ 4:30 pm 2-3-79. drilled to 1550' TD for
SURF CSG. SET 958", 36", K-55, ST & C @ 1550' KB. Cmt'd w/
100sx Class C cmt, Jail in w 200sx Class C cmt.
Circ. 100sx to surf. W.O.C. 18 hrs. Pres test to 1000 psi
for 30 mins. Held ok.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Butterfield TITLE Chief Engineer DATE 2-3-79

(This space for Federal or State use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

2065 5

7772 4

File

ACCEPTED FOR RECORD

FEB 7 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side